



DROP PROFILE LT SMART 601

USAGE:

The Drop Profile LT is a distinctively designed profile specifically intended for the seamless completion of the upper boundaries of windows and/or doors. Its primary function is to ensure the efficient drainage of any excess water from horizontal surfaces, thus preventing any water infiltration into the insulation system.

Profile	Mesh Size (cm)	Length (m)	Packaging (pc)
SMART 601	10 x 10	2.0	20

ADVANTAGES:

Aesthetic Appeal: Allows for easy crafting of a visually appealing structural finish.

Robust Protection: Effectively safeguards the edges from potential mechanical harms.

Efficient Water Management: The profile's vein feature ensures prompt and efficient drainage of surplus water.

Crack Prevention: Assists in warding off the emergence of cracks at connection junctures.

Sleek Design: Once installed and finished, the vein feature becomes seamlessly integrated and unnoticeable.

INSTALLATION:

Starting Point: Begin by enveloping the insulation board with a reinforcement compound.

Alignment: Properly align the drop profile.

Mesh Application: Press the profile's mesh into the mixture, and smoothen any emerged mixture until a uniform spread is achieved.

Layering: Progressively encase the remaining mesh with continuous layers of the mixture.

Integration: While connecting this profile with another or using a fiberglass-reinforcing net, ensure a 10 cm overlap for the nets.

MATERIAL:

Profile is constructed from an alkali-resistant PVC material, augmented with a glass fiber reinforcement mesh that complies with the ETAG 004 standards

Complete Guide for Handling, Storing, and Installing Insulation and Plaster Profiles SMART

By adhering to these guidelines, you can ensure the longevity and optimal performance of your insulation and plaster profiles SMART.

STORAGE RECOMMENDATIONS

- **Positioning/Orientation:** Regardless of the type, profiles should always be stored horizontally to avoid deformation or any weakening of adhesive bonds.
- **Environment & Conditions:** A dry storage environment is crucial. Shield the profiles from prolonged exposure to sunlight, extreme heat, and mechanical disturbances. Maintain storage temperatures between -5°C and +40°C for optimal results.
- **Storage Duration:** Adhere to the maximum storage duration of 18 months for optimal shelf life.
- **Chemical Exposure:** Ensure the storage area is devoid of any aggressive chemicals or solvents that might degrade the profile's material.

HANDLING & PRECAUTIONS

- **Protective Gear:** Always employ the right protective gloves and eyewear when managing and installing the profiles.
- **Safe Movement:** Utilize correct lifting and transport techniques to prevent unnecessary bending, dragging, or warping of the profiles. For bulk transportation, use a dolly or cart.
- **Tool Usage/Modifications:** For any adjustments or modifications, use clean, sharp, and sanitized tools to prevent potential damage or uneven edges.
- **Cleaning Protocol:** If the profile becomes dirty, clean it gently with a damp cloth and let it dry completely. Avoid using abrasive or corrosive cleaners.
- **Surface Preparation:** Before installation, ensure the surface is free from dust, grease, or any contaminants for better adhesion and longevity.
- **Environmental Conditions for Installation:** Always install the profile in conditions between +5°C and +40°C. Avoid installation during extreme weather conditions such as heavy rain, strong winds, or frost.

WASTE MANAGEMENT

- **Material Waste:** Dispose of material remnants in compliance with EAK 101103 for old fiberglass materials or EAK 170904 for mixed construction and demolition waste. Proper waste disposal is essential for environmental sustainability.

PRODUCT SPECIFICATIONS AND COMPATIBILITY

- **Material Composition:** Be aware of the specific materials used in the construction of the profiles, as this could affect its insulation capabilities, longevity, and suitability for specific projects.
- **Size and Dimensions:** Knowing the exact size and dimensions of the profiles can help in accurate planning and utilization.

Load-Bearing Capacity: Some profiles might have a load-bearing capacity that should not be exceeded during installation or usage.